



GLADSTONE
TRUCK/BUS TIRES

HIGHWAY



MINING ROAD



MIX ROAD



DESERT ROAD





HIGHWAY



GT817

Applicable Vehicle Model & Road condition



Features & Benefits

- Four consecutive main grooves and three auxiliary fine grooves provide outstanding drainage and grip performance.
- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Improved tread design, High wear resistance and eccentric wear resistance.
- Low rolling resistance, Save fuel consumption.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
11.00R20	18PR	8.00	L	152	149	3550	3250	930	930	293	1085	17
11R22.5	18PR	8.25	M	149	146	3250	3000	930	930	279	1054	14.5
11R24.5	16PR	8.25	M	149	146	3250	3000	830	830	200	1104	14
12R22.5	18PR	9.00	M	152	149	3550	3250	930	930	300	1084	15
295/75R22.5	16PR	9.00	L	146	143	3000	2725	830	830	298	1014	14.5
295/80R22.5	18PR	9.00	M	152	149	3550	3250	900	900	298	1044	14.5
315/80R22.5	20PR	9.00	M	156	150	4000	3350	850	850	312	1076	14.5

GT818

Applicable Vehicle Model & Road condition



Features & Benefits

- 3 continuous ribs, and the circumferential grooves enhances superior adhesion properties of the ground, excellent wet skid resistance, special tread design, providing a low heating up, wear resistance.
- Design of big pattern block in the middle of tread provides good abrasion resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
12R22.5	18PR	9.00	M	152	149	3550	3250	930	930	300	1084	15

GT836

Applicable Vehicle Model & Road condition



Features & Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Irregular abrasion and cutting resistance compound to achieve longer mileage
- Provide excellent heat dissipation and high speed performance
- With good performance in anti-cracking and tear resistance



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
11.00R20	18PR	8.00	J	152	149	3550	3250	930	930	224	1085	17
12.00R20	20PR	8.50	L	156	153	4000	3650	900	900	230	1125	16
12R22.5	18PR	9.00	M	152	149	3550	3250	930	930	226	1085	15

GT831

Applicable Vehicle Model & Road ondition



Features & Benefits

- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Irregular abrasion and cutting resistance compound to achieve longer mileage
- Provide excellent heat dissipation and high speed performance
- With good performance in anti-cracking and tear resistance



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
9.00R20	18PR	7.00	L	144	142	2800	2650	900	900	259	1019	15.5
10.00R20	18PR	7.50	L	146	143	3000	2725	830	830	278	1054	16.5
11.00R20	18PR	8.00	L	152	149	3550	3250	930	930	293	1085	17
12.00R20	20PR	8.50	L	156	153	4000	3650	900	900	315	1125	16
12.00R24	20PR	8.50	K	160	157	4500	4125	900	900	315	1226	14.5
11R22.5	18PR	8.25	M	149	146	3250	3000	930	930	279	1054	14.5
12R22.5	18PR	9.00	M	152	149	3550	3250	930	930	300	1084	15
13R22.5	18PR	9.75	M	154	151	3750	3450	830	830	320	1124	17
315/80R22.5	20PR	9.00	M	156	150	4000	3350	850	850	312	1076	14.5

GT851

Applicable Vehicle Model & Road ondition



Features & Benefits

- Excellent traction performance, water draining performance, high speed running, well loading capacity
- Design of five pattern grooves provide better slip and wet resistance as well as safe handling.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
385/65R22.5	20PR	11.75	K	160	---	4500	---	900	---	389	1072	16.5

GT859

Applicable Vehicle Model & Road ondition



Features & Benefits

- Four consecutive main grooves and three auxiliary fine grooves to provide better drainage and grip performance
- Design of proper proportion for block and groove to provide better wear resistance performance;
- Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage. Excellent fuel efficiency.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
385/65R22.5	20PR	11.75	K	160	---	4500	---	900	---	389	1072	14.5

GT869

Applicable Vehicle Model & Road ondition



Features & Benefits

- Four consecutive main grooves and three auxiliary fine grooves to provide better drainage and grip performance
- Design of proper proportion for block and groove to provide better wear resistance performance;
- Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage. Excellent fuel efficiency.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
385/65R22.5	20PR	11.75	K	160	---	4500	---	900	---	389	1072	14.5

HS201

Applicable Vehicle Model & Road ondition



Features & Benefits

- Suitable for medium/long-haul vehicles running on the high-grade road, excellent load capacity
- Straight shallow grooves offer an excellent drive, straight ride, and anti-sidewall scuffing performance.
- Suitable for the all-wheel position, running on the national highway.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)	
				S	D	S	D	S	D	SW	OD
315/70R22.5	20PR	9.00	M	154	150	3750	3350	900	900	330	1015

HS205

Applicable Vehicle Model & Road ondition



Features & Benefits

- Improved tread design, high wear resistance, and eccentric wear resistance.
- Low rolling resistance, save fuel consumption, and good handling quality.
- Trailer tires are suitable for long-distance transportation, running on high-grade roads.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)	
				S	D	S	D	S	D	SW	OD
205/75R17.5	16PR	6.00	M	124	122	1600	1500	750	750	213	750
215/75R17.5	16PR	6.00	M	126	124	1700	1600	700	700	214	759
225/70R19.5	16PR	6.75	M	128	126	1800	1700	760	760	230	812
235/75R17.5	16PR	6.75	M	132	130	2000	1900	775	775	232	790
245/70R19.5	16PR	7.50	M	136	134	2180	2060	830	830	252	835
255/70R22.5	16PR	7.50	M	140	137	2500	2300	830	830	260	931
265/70R19.5	16PR	7.50	M	140	138	2500	2360	775	775	266	862
275/70R22.5	16PR	8.25	M	148	145	3150	2900	900	900	280	958
285/75R24.5	16PR	8.25	L	147	144	3075	2800	830	830	285	1055
295/75R22.5	16PR	9.00	L	146	143	3000	2725	830	830	302	1008

HS206

Applicable Vehicle Model & Road condition



Features & Benefits

- High wear resistance, high-cost performance
- Suitable for all positions of buses and light trucks running on highways and roads of common grades.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)	
				S	D	S	D	S	D	SW	OD
9.5R17.5	18PR	6.75	M	143	141	2725	2575	930	930	241	845

HS268

Applicable Vehicle Model & Road condition



Features & Benefits

- Super abrasion resistance, excellent heat dissipation performance
- Good handling, and traction, with higher original mileage, and excellent fuel efficiency.
- Suitable for the all-wheel position, medium/long-haul vehicles, running on mixed pavements.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)	
				S	D	S	D	S	D	SW	OD
6.50R16LT	12PR	5.50F	L	110	105	1060	925	670	670	185	750
7.00R16LT	14PR	5.50F	L	118	114	1320	1180	770	770	200	775
7.50R16LT	14PR	6.00G	L	122	118	1500	1320	770	770	215	805
8.25R16LT	16PR	6.50H	L	128	124	1800	1600	770	770	235	855
8.25R20	16PR	6.50	K	139	137	2430	2300	930	930	236	974

GR612

Applicable Vehicle Model & Road condition



Features & Benefits

- Applicable to the national highway, high speed, and high grade pavement;
- Especially suitable for medium and long-distance transportation, with good guiding performance;
- Features: anti-sideslip, good drainage, heat dissipation performance, stone ejector pattern design, long mileage.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
285/70R19.5	18PR	8.25	J	150	148	3350	3150	900	900	--	--	13.0

GR662

Applicable Vehicle Model & Road condition



Features & Benefits

- Suitable for national roads, high-speed and high-grade paved roads;
- Effectively prevents side slips and provides good carrying performance;
- Good heat dissipation and stone ejector;
- Excellent durability and wear resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
275/80R22.5	16PR	8.25	M	149	146	3250	3000	850	850	--	--	14.0

GR666

Applicable Vehicle Model & Road condition



Features & Benefits

- Suitable for national road, high-speed, and high-grade paving roads;
- Provide excellent steering and anti-skid performance;
- Good performance self-cleaning in addition to stone removal, prevent tread cracks;
- Reduce tread heat and have good abrasion resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
425/65R22.5	20PR	12.25	K	165	--	5150	--	825	--	318	1124	15.0
445/65R22.5	20PR	13.00	K	169	--	5800	--	900	--	350	1150	15.0

GR777

Applicable Vehicle Model & Road condition



Features & Benefits

- Suitable for national high-way and high-grade paved roads;
- Improved pattern design effectively avoids uneven wear;
- Better grip with excellent driving and braking performance;
- Excellent wear resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
425/65R22.5	20PR	12.25	J	165	--	5150	--	825	--	318	1124	17.5
445/65R22.5	20PR	13.00	K	169	--	5800	--	900	--	350	1150	18.0



GR881

Applicable Vehicle Model & Road condition



Features & Benefits

- Applicable to national high-way, high-speed and high-various comprehensive pavements;
- Especially suitable for medium and long-distance transportation, with good steering performance;
- Features: anti-sideslip, good drainage performance and heat dissipation performance, stone ejector design, high mileage.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
325/95R24	22PR	9.00	K	162	160	4750	4500	930	930	226	1228	17.5

S02

Applicable Vehicle Model & Road condition



Features & Benefits

- Block tread pattern provides excellent gripping and traction power.
- Tough belt construction for smooth wear and longer mileage.
- Special tread compound for high resistance against tread cut.
- Suitable for all positions of trucks running on non-paved roads.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
8R22.5	14PR	6.00	M	130	128	1900	1800	830	830	170	935	14
9R22.5	14PR	6.75	M	136	134	2240	2120	830	830	185	974	14
10R22.5	16PR	7.50	L	144	142	2800	2650	900	900	200	1019	15

GLADSTONE



MIX ROAD



GT615

Applicable Vehicle Model & Road ondition



Features & Benefits

- Deeper pattern with formulation of abrasion resistance and low heating performance for longer miles
- Open shoulder and block type pattern provides strong traction and gripping stress
- Open groove and bottom design given excellent self-cleaning performance
- Reinforced bead and body to strengthen the puncture resistance, tear resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
9.00R20	18PR	7.00	L	144	142	2800	2650	900	900	259	1019	16
10.00R20	18PR	7.50	L	149	146	3000	2775	830	830	278	1054	17
11.00R20	18PR	8.00	L	152	149	3550	3250	930	930	293	1085	17.5
12.00R20	20PR	8.50	L	156	153	4000	3650	900	900	315	1125	18.5

GT661

Applicable Vehicle Model & Road ondition



Features & Benefits

- Suitable for driving wheels on short non paved road condition, (mining, mountain, construction site, etc.)
- Excellent driving and braking performance.
- Superior tear and rear resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
12R22.5	18PR	9.00	L	152	149	3550	3250	930	930	300	1084	19

GT663

Applicable Vehicle Model & Road ondition



Features & Benefits

- Deeper pattern with formulation of abrasion resistance and low heating performance for longer miles
- Open shoulder and block type pattern provides strong traction and gripping stress
- Open groove and bottom design given excellent self-cleaning performance
- Reinforced bead and body to strengthen the puncture resistance, tear resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
11R22.5	16PR	8.25	L	146	143	3000	2725	830	830	279	1054	19.5
11R24.5	16PR	8.25	L	149	146	3250	3000	830	830	279	1116	19.5
295/75R22.5	16PR	9.00	L	146	143	3000	2725	830	830	298	1014	19.5

GT665

Applicable Vehicle Model & Road ondition



Features & Benefits

- Open shoulder design, broader horizontal groove, provide powerful traction and grip
- High performance tire tread design, increase anti-abrasion performance
- Mixed pattern design provide excellent traction performance and braking power...
- Anti-stone structure design at the bottom of pattern groove, increase anti-puncture performance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
11R22.5	16PR	8.25	L	146	143	3000	2725	830	830	279	1050	18.5
13R22.5	18PR	9.75	L	154	151	3750	3450	830	830	235	1124	18.5

GT666

Applicable Vehicle Model & Road ondition



Features & Benefits

- Special groove provides pattern selfclean performance and protect the bottom of groove;
- Mixed pattern design provide excellent traction performance and braking power...
- Tire adopt super structure, with excellent carrying capacity, super wear-resistant and anti-puncture performance
- Special groove provides pattern selfclean performance and protect the bottom of groove;
- Widened tread improves tire grounded pressure, one-way pattern groove provides better wet and slip resistance;
- Open shoulder improves tire's heat dissipation.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
12R22.5	18PR	9.00	L	152	149	3550	3250	930	930	300	1084	19
295/80R22.5	18PR	9.00	L	152	149	3550	3250	900	900	298	1044	19.5
315/80R22.5	20PR	9.00	L	156	150	4000	3350	850	850	312	1082	19

GT667

Applicable Vehicle Model & Road ondition



Features & Benefits

- "Super abrasion resistance, excellent heat dissipation performance"
- good handling and traction, with higher original mileage
- Excellent fuel efficiency.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
12R22.5	18PR	9.00	L	152	149	3550	3250	930	930	300	1084	19
295/80R22.5	18PR	9.00	L	152	149	3550	3250	900	900	298	1044	19.5
315/80R22.5	20PR	9.00	L	156	150	4000	3350	850	850	312	1076	19

GT668

Applicable Vehicle Model & Road ondition



Features & Benefits

- Design of wide rib grooves with lug grooves provides better water dispersion and wet resisting performance
- Design of pattern blocks offers excellent traction performance
- Open groove and bottom design given excellent self-cleaning performance
- Reinforced bead and body to strengthen the puncture resistance, tear resistance
- Open shoulder and block type pattern provides strong traction and gripping stress.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
11.00R20	18PR	8.00	L	152	149	3550	3250	930	930	293	1085	17.5
12.00R20	20PR	8.50	L	156	153	4000	3650	900	900	315	1125	18.5

GT669

Applicable Vehicle Model & Road ondition



Features & Benefits

- Design of wide rib grooves with lug grooves provides better water dispersion and wet resisting performance
- Design of pattern blocks offers excellent traction performance
- Open groove and bottom design given excellent self-cleaning performance
- Reinforced bead and body to strengthen the puncture resistance, tear resistance
- Open shoulder and block type pattern provides strong traction and gripping stress.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
12.00R20	20PR	8.50	L	156	153	4000	3650	900	900	315	1125	18.5
13R22.5	18PR	9.75	L	154	151	4000	3350	830	830	320	1124	21

GT819

Applicable Vehicle Model & Road ondition



Features & Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Irregular abrasion and cutting resistance compound to achieve longer mileage
- Provide excellent heat dissipation and high speed performance
- With good performance in anti-cracking and tear resistance



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
12.00R24	20PR	8.50	K	160	157	4500	4125	900	900	315	1226	14.5

GLADSTONE

GT832

Applicable Vehicle Model & Road ondition



Features & Benefits

- Provide excellent anti-sidesliping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Irregular abrasion and cutting resistance compound to achieve longer mileage
- Provide excellent heat dissipation and high speed performance
- With good performance in anti-cracking and tear resistance



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
12.00R24	20PR	8.50	K	160	157	4500	4125	900	900	315	1226	14.5

GR678

Applicable Vehicle Model & Road ondition



Features & Benefits

- Suitable for long-distance mixed road transportation
- The rubber in the middle of the crown is highly saturated, durable, and wear-resistant
- The longitudinal groove design has good heat dissipation performance
- Excellent block pattern design to achieve maximum power transmission



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
275/80R22.5	16PR	8.25	M	149	146	3250	3000	850	850	225	1012	19.0
285/70R19.5	18PR	8.25	J	150	148	3350	3150	900	900	220	895	16.0

GR882

Applicable Vehicle Model & Road ondition



Features & Benefits

- A large horizontal tread pattern provides high-strength tread formula
- Improved tread adhesive enhances anti-cutting performance
- Strong structure improves overload performance



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
325/95R24	22PR	9.00	K	162	160	4750	4500	930	930	238	1228	20.0

GLADSTONE

GR982

Applicable Vehicle Model & Road condition



Features & Benefits

- Suitable for the short-distance mixed road;
- It is especially suitable for short-distance work with high load
- The optimized tread design effectively avoids uneven wear;
- The low heat composite matrix ensures high mileage, and the small zigzag tread design improves grip.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
325/95R24	22PR	9.00	K	162	160	4750	4500	930	930	238	1228	15.5

GR897

Applicable Vehicle Model & Road condition



Features & Benefits

- The tire adopts special tread formula.
- The crown part adopts high-wear-resisting rubber;
- The inner layer adopts low-hot-rolled rubber;
- Unique tire shoulder design enhances the anti-wear performance and prevent abnormal wear
- Good drainage performance, good driving stability, low fuel consumption, low noise.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
325/95R24	22PR	9.00	K	162	160	4750	4500	850	850	238	1228	15.5

HS202

Applicable Vehicle Model & Road condition



Features & Benefits

- A mixed pattern design provides strong traction and braking power.
- Longer block pattern designs enhance the ability of unit eccentric wear and abnormal wear.
- Five deep grooves, multi block&tiny kerfs on the blocks assure a firm grip and a powerful
- Suitable for driving wheel position in good road condition.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)	
				S	D	S	D	S	D	SW	OD
315/70R22.5	20PR	9.00	M	154	150	3750	3350	900	900	330	1025

HS208

Applicable Vehicle Model & Road condition



Features & Benefits

- Widen tread with design provides excellent driving and gripping power.
- The extra-deep tread provides extra powerful traction and long tread life.
- The closed shoulder maintains a good irregular wear resistance.
- With excellent crack and tear resistance character.
- Suitable for light, heavy-duty, and bus all positions on the good or non-paved roads.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)	
				S	D	S	D	S	D	SW	OD
285/75R24.5	16PR	8.25	L	147	144	3075	2800	830	830	285	1055
295/75R22.5	16PR	9.00	L	146	143	3000	2725	830	830	302	1016

HS918

Applicable Vehicle Model & Road condition



Features & Benefits

- A big deep block provides strong traction and braking power.
- The open groove and bottom design gave an excellent self-cleaning performance.
- Reinforced bead and body to strengthen the puncture resistance, and tear resistance.
- Suitable for short mileage vehicles running on various non-paved roads.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)	
				S	D	S	D	S	D	SW	OD
7.00R16LT	14PR	5.50F	L	118	114	1320	1180	770	770	200	775
7.50R16LT	14PR	6.00G	L	122	118	1500	1320	770	770	215	805
8.25R16LT	16PR	6.50L	K	128	124	1800	1600	770	770	235	855
8.25R20	16PR	6.50	K	139	137	2430	2300	930	930	236	972

HS928

Applicable Vehicle Model & Road condition



Features & Benefits

- Block tread pattern provides excellent gripping and traction power.
- Tough belt construction for smooth wear and longer mileage.
- Special tread compound for high resistance against tread cut.
- Suitable for all positions of trucks running on non-paved roads.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)	
				S	D	S	D	S	D	SW	OD
9.5R17.5	18PR	6.75	M	143	141	2725	2575	930	930	240.5	844
215/75R17.5	16PR	6.00	M	126	124	1700	1600	700	700	214	770
235/75R17.5	16PR	6.75	M	132	130	2000	1900	775	775	232	789

GLADSTONE



MINING ROAD



GT816

Applicable Vehicle Model & Road condition



Features & Benefits

- Deeper pattern with formulation of abrasion resistance and low heating performance for longer miles
- Open shoulder and block type pattern provides strong traction and gripping stress
- Open groove and bottom design given excellent self-cleaning performance
- Reinforced bead and body to strengthen the puncture resistance, tear resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
12R22.5	18PR	9.00	L	152	149	3550	3250	930	930	230	1096	23

GT933

Applicable Vehicle Model & Road condition



Features & Benefits

- Interlaced reinforcing rib design at the pattern block bottom provides better tear resistance performance;
- Stone emitter at the bottom of grooves protects tire carcass effectively.
- Improved traction, driving and braking performance
- With strong ground grip, good self-cleaning, good standing wear and high in loading ability



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
11.00R20	18PR	8.00	F	152	149	3550	3250	930	930	293	1095	23
12.00R20	20PR	8.50	F	156	153	4000	3650	900	900	315	1135	23.5

GT939

Applicable Vehicle Model & Road condition



Features & Benefits

- Interlaced reinforcing rib design at the pattern block bottom provides better tear resistance;
- Stone emitter at the bottom of grooves protects tire carcass effectively.
- Improved traction, driving and braking performance
- With strong ground grip, good self-cleaning, good standing wear and high in loading ability



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
11.00R20	18PR	8.00	F	152	149	3550	3250	930	930	293	1085	23
12.00R20	20PR	8.50	F	156	153	4000	3650	900	900	315	1135	23.5

GLADSTONE



Y811

Applicable Vehicle Model & Road condition



Features & Benefits

- Deeper pattern with formulation of abrasion resistance and low heating performance for longer miles.
- Open shoulder and block type pattern provides strong traction and gripping stress.
- Open groove and bottom design given excellent self-cleaning performance.
- Reinforced bead and body to strengthen the puncture resistance, tear resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
14.00R20	20PR	10.00	J	164	161	5000	4625	790	790	----	----	20.5

Y816

Applicable Vehicle Model & Road condition



Features & Benefits

- Deeper pattern with formulation of abrasion resistance and low heating performance for longer miles.
- Open shoulder and block type pattern provides strong traction and gripping stress.
- Open groove and bottom design given excellent self-cleaning performance.
- Reinforced bead and body to strengthen the puncture resistance, tear resistance.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
14.00R20	20PR	10.00	J	164	161	4625	4250	690	690	----	----	20

DESERT ROAD

ZT208

Applicable Vehicle Model & Road condition



Features & Benefits

- Block tread pattern provides excellent gripping and traction power.
- Tough belt construction for smooth wear and longer mileage.
- Special tread compound for high resistance against tread cut.
- Suitable for all positions of trucks running on non-paved roads.



SIZE	PLY	STANDARD RIM	SPEED RATING	LOAD INDEX		MAX LOAD (KG)		PRESSURE (KPA)		ID (MM)		TREAD DEPTH
				S	D	S	D	S	D	SW	OD	
7.50R16LT	8PR	6.00G	M	112	107	1120	975	460	460	215	805	21